

HIKARI® Innovative Electronic Button Attaching Machine

Feel the innovation and efficiency

HK-438D Computerized High-Speed Direct-Drive Button Attaching Machine

The HIKARI innovative electronic button attaching machine is optimized for the European requirements: small and middle sized orders, hard to sew fabrics, and high quality production.



OUTSTANDING TECHNOLOGICAL FLEXIBILITY WHAT MAKES HIKARI COMPUTERIZED DIRECT-DRIVE BUTTON ATTACHING MACHINE UNIQUE IN THE MARKET

- High quality stable button attaching on max. 2700 RPM
- Cycle sew, and 49 factory pre-defined pattern data in the memory of the machine
- Maintenance free direct-drive system for 35 % less power consumption compared to belt drive models



HIKARI® Innovative Electronic Button Attaching Machine

Feel the innovation and efficiency

What does it mean to use HIKARI machines in production?

Stay focused on the advantages offered by HIKARI:

1. It is possible to build a homogenous plant with HIKARI, because we can supply a wide variety of machines and special machines for the sewing room.
2. The strength of HIKARI is the strong development of the most applicable machines in the sewing room. Therefore, the biggest efficiency, the highest saving on electricity bills, and the lowest maintenance costs is provided in case of using the HIKARI machines:
 - Innovative Single Needle Lock Stitch Machines: H9180 series, H8800D series
 - Innovative Overlock Machines: HX6800TA/AK series

TECHNICAL SPECIFICATIONS

Model	HK438D	HK438DL	HK438DS
Application	Normal-duty fabrics	Vertical position	Casual garments
Max sewing speed	Max. 2700		
Needle type	DPX17		
Stitch length	0,05 - 12,7 mm		
Presser foot height	13 mm		
Button diameter	8-30 mm (Option: Over 25mm other button gripper is needed)		
Rotary hook	Shuttle hook		
Thread trimmer	Automated		
Thread wiper	Automated		
Thread nipper	Automated		
Number of user programs	49		
Number of cycle programs	9		
Number of user defined programs	Max 200 pcs. (200.000 stitches)		
Drive mode	AC servo motor 550W		
Power supply	Single phase 110V/220V, Three phase: 200V/380V, 400W		
Lubrication shuttle hook	High speed spindle oil		
Lubrication needle bar	Special HIKARI grease		

